

Levels of Knowledge and Belief

Computational Social Choice Seminar

Eric Pacuit

Tilburg University

`ai.stanford.edu/~epacuit`

November 13, 2009

Introduction and Motivation

Informal Definition: Given some fact P and a set of agents \mathcal{A} , a **state of knowledge** is a (consistent) description of the agents first-order and higher-order information about P .

Introduction and Motivation

Informal Definition: Given some fact P and a set of agents \mathcal{A} , a **state of knowledge** is a (consistent) description of the agents first-order and higher-order information about P .

For example: $\{P, K_A P, K_B P, K_B K_A P\}$

Introduction and Motivation

Informal Definition: Given some fact P and a set of agents \mathcal{A} , a **state of knowledge** is a (consistent) description of the agents first-order and higher-order information about P .

For example: $\{P, K_A P, K_B P, K_B K_A P\}$

Also called **level of knowledge**, **hierarchy of knowledge**.

Introduction and Motivation

Informal Definition: Given some fact P and a set of agents \mathcal{A} , a **state of knowledge** is a (consistent) description of the agents first-order and higher-order information about P .

For example: $\{P, K_A P, K_B P, K_B K_A P\}$

Also called **level of knowledge**, **hierarchy of knowledge**.

At one extreme, no one may have any information about P and the other extreme is when there is common knowledge of P .

There are many interesting levels in between...

Introduction and Motivation

Informal Definition: Given some fact P and a set of agents \mathcal{A} , a **state of knowledge** is a (consistent) description of the agents first-order and higher-order information about P .

For example: $\{P, K_i P, K_j P, K_j K_i P\}$

Also called **level of knowledge**, **hierarchy of knowledge**.

At one extreme, no one may have any information about P and the other extreme is when there is **common knowledge** of P .

There are many interesting levels in between...

Introduction and Motivation

Informal Definition: Given some fact P and a set of agents \mathcal{A} , a **state of belief** is a (consistent) description of the agents first-order and higher-order information about P .

For example: $\{P, B_i P, B_j P, B_j B_i P\}$

Also called **level of belief**, **hierarchy of belief**.

At one extreme, no one may have any information about P and the other extreme is when there is **common belief** of P .

There are many interesting levels in between...

Introduction and Motivation

Motivating Questions/Issues:

- ▶ How do states of knowledge influence decisions in *game situations*?
- ▶ Can we *realize* any state of knowledge?
- ▶ What is a *state* in an epistemic model?
- ▶ Is an epistemic model *common knowledge* among the agents?

States of Knowledge in Games

R. Parikh. *Levels of knowledge, games and group action*. Research in Economics 57, pp. 267 - 281 (2003).

States of Knowledge in Games

	G	N
g		
n		

States of Knowledge in Games

	G	N
g		$(1, 0)$
n	$(0, 1)$	

States of Knowledge in Games

	G	N
g		$(1, 0)$
n	$(0, 1)$	$(0, 0)$

States of Knowledge in Games

	G	N
g	$(-100, -10)$	$(1, 0)$
n	$(0, 1)$	$(0, 0)$

States of Knowledge in Games

	G	N
g	$(-100, -10)$	$(1, 0)$
n	$(0, 1)$	$(0, 0)$

States of Knowledge in Games

	G	N
g	$(-100, -10)$	$(1, 0)$
n	$(0, 1)$	$(0, 0)$

States of Knowledge in Games

	G	N
g	$(-100, -10)$	$(1, 0)$
n	$(0, 1)$	$(0, 0)$

$C_{p,mC}$

States of Knowledge in Games

	G	N
g	$(-100, -10)$	$(1, 0)$
n	$(0, 1)$	$(0, 0)$

$$K_p c, \neg K_m K_p c$$

Realizing States of Knowledge

What is the exact relationship between

Realizing States of Knowledge

What is the exact relationship between 1. types of communicatory events (public broadcasts, private announcements, DEL events, etc.),

Realizing States of Knowledge

What is the exact relationship between 1. types of communicatory events (public broadcasts, private announcements, DEL events, etc.), 2. the *protocol* (eg., synchronous, asynchronous, communication graph) and

Realizing States of Knowledge

What is the exact relationship between 1. types of communicatory events (public broadcasts, private announcements, DEL events, etc.), 2. the *protocol* (eg., synchronous, asynchronous, communication graph) and 3. different levels of knowledge?

Realizing States of Knowledge

What is the exact relationship between 1. types of communicatory events (public broadcasts, private announcements, DEL events, etc.), 2. the *protocol* (eg., synchronous, asynchronous, communication graph) and 3. different levels of knowledge?

Classic example: general's problem or the email problem show that common knowledge cannot be realized in systems with only asynchronous communication.

(cf. Halpern and Moses, Rubinstein)

Realizing States of Knowledge

What is the exact relationship between 1. types of communicatory events (public broadcasts, private announcements, DEL events, etc.), 2. the *protocol* (eg., synchronous, asynchronous, communication graph) and 3. different levels of knowledge?

Classic example: general's problem or the email problem show that common knowledge cannot be realized in systems with only asynchronous communication.

(cf. Halpern and Moses, Rubinstein)

What about other levels of knowledge?

R. Parikh and P. Krasucki. *Levels of knowledge in distributed computing*. Sadhana-Proceedings of the Indian Academy of Science 17 (1992).

What is a *State*?

Possible worlds, or states, are taken as primitive in Kripke structures. But in many applications, we intuitively understand what a state *is*:

What is a *State*?

Possible worlds, or states, are taken as primitive in Kripke structures. But in many applications, we intuitively understand what a state *is*:

Dynamic logic: a program state (assignment of values to variables)

Temporal logic: a moment in time

Distributed system: a sequence of local states for each process

What is a *State*?

Possible worlds, or states, are taken as primitive in Kripke structures. But in many applications, we intuitively understand what a state *is*:

Dynamic logic: a program state (assignment of values to variables)

Temporal logic: a moment in time

Distributed system: a sequence of local states for each process

What about in *game situations*?

What is a *State*?

Possible worlds, or states, are taken as primitive in Kripke structures. But in many applications, we intuitively understand what a state *is*:

Dynamic logic: a program state (assignment of values to variables)

Temporal logic: a moment in time

Distributed system: a sequence of local states for each process

What about in *game situations*?

Answer: a *description* of the first-order and higher-order information of the players

R. Fagin, J. Halpern and M. Vardi. *Model theoretic analysis of knowledge*. Journal of the ACM 91 (1991).

Is an Epistemic Model “Common Knowledge”?

“The implicit assumption that the information partitions...are themselves common knowledge...constitutes no loss of generality... the assertion that each individual ‘knows’ the knowledge operators of all individual has no real substance; it is part of the framework.”

R. Aumann. *Interactive Epistemology I & II*. International Journal of Game Theory (1999).

Is an Epistemic Model “Common Knowledge”?

“The implicit assumption that the information partitions...are themselves common knowledge...constitutes no loss of generality... the assertion that each individual ‘knows’ the knowledge operators of all individual has no real substance; it is part of the framework.”

R. Aumann. *Interactive Epistemology I & II*. International Journal of Game Theory (1999).

“it is an informal but *meaningful* meta-assumption....It is not trivial at all to assume it is “common knowledge” which partition every player has.”

A. Heifetz. *How canonical is the canonical model? A comment on Aumann's interactive epistemology*. International Journal of Game Theory (1999).

A General Question

How many levels/states of knowledge (beliefs) are there?

A General Question

How many levels/states of knowledge (beliefs) are there?

It depends on how you count:

- ▶ Parikh and Krasucki: Countably many *levels* of knowledge
- ▶ Parikh and EP: Uncountably many levels of belief
- ▶ Hart, Heiftetz and Samet: Uncountably many *states* of knowledge

Levels of Knowledge

Fix a set of agents $\mathcal{A} = \{1, \dots, n\}$.

$\Sigma_K = \{K_1, \dots, K_n\}$ and $\Sigma_C = \{C_U\}_{U \subseteq \mathcal{A}}$

Level of Knowledge: $Lev_{\mathcal{M}}(p, s) = \{x \in \Sigma^* \mid \mathcal{M}, s \models xp\}$
(where $\Sigma = \Sigma_K$ or $\Sigma = \Sigma_C$).

[If Σ is a finite set, then Σ^* is the set of finite strings over Σ]
[Recall the definition of truth in a Kripke structure]

Levels of Knowledge

Fix a set of agents $\mathcal{A} = \{1, \dots, n\}$.

$\Sigma_K = \{K_1, \dots, K_n\}$ and $\Sigma_C = \{C_U\}_{U \subseteq \mathcal{A}}$

Level of Knowledge: $Lev_{\mathcal{M}}(p, s) = \{x \in \Sigma^* \mid \mathcal{M}, s \models xp\}$
(where $\Sigma = \Sigma_K$ or $\Sigma = \Sigma_C$).

[If Σ is a finite set, then Σ^* is the set of finite strings over Σ]
[Recall the definition of truth in a Kripke structure]

R. Parikh and P. Krasucki. *Levels of knowledge in distributed computing*. Sadhana-Proceedings of the Indian Academy of Science 17 (1992).

R. Parikh. *Levels of knowledge, games and group action*. Research in Economics 57, pp. 267 - 281 (2003).

Levels of Knowledge

A level of knowledge is simply a set of finite strings over Σ_C .
Why isn't it obvious that there are *uncountably* many levels of knowledge?

Levels of Knowledge

A level of knowledge is simply a set of finite strings over Σ_C .
Why isn't it obvious that there are *uncountably* many levels of knowledge?

Consider the sets:

- ▶ $L_1 = \{K_1, K_2\}$ and $L_2 = \{K_1, K_2, K_1K_2\}$
- ▶ $L_1 = \{K_1, K_3, K_1K_2K_3\}$ and $L_2 = \{K_1, K_2, K_3, K_1K_2K_3\}$

Levels of Knowledge

A level of knowledge is simply a set of finite strings over Σ_C .
Why isn't it obvious that there are *uncountably* many levels of knowledge?

Consider the sets:

- ▶ $L_1 = \{K_1, K_2\}$ and $L_2 = \{K_1, K_2, K_1K_2\}$
(*different level of knowledge*)
- ▶ $L_1 = \{K_1, K_3, K_1K_2K_3\}$ and $L_2 = \{K_1, K_2, K_3, K_1K_2K_3\}$
(*same level of knowledge*)

Levels of Knowledge: Preliminaries

Given any two strings $x, y \in \Sigma^*$, we say x is **embeddable** in y , written $x \leq y$, if all symbols of x occur in y in the same order but not necessarily consecutively.

Levels of Knowledge: Preliminaries

Given any two strings $x, y \in \Sigma^*$, we say x is **embeddable** in y , written $x \leq y$, if all symbols of x occur in y in the same order but not necessarily consecutively. Formally, we can define \leq as follows:

1. $x \leq x$ and $\epsilon \leq x$ for all $x \in \Sigma^*$
2. $x \leq y$ if there exists x', x'', y', y'' , ($y, y'' \neq \epsilon$) such that $x = x'x''$, $y = y'y''$ and $x' \leq y'$, $x'' \leq y''$.

\leq is the smallest relation satisfying (1) and (2).

Levels of Knowledge: Preliminaries

Given any two strings $x, y \in \Sigma^*$, we say x is **embeddable** in y , written $x \leq y$, if all symbols of x occur in y in the same order but not necessarily consecutively. Formally, we can define \leq as follows:

1. $x \leq x$ and $\epsilon \leq x$ for all $x \in \Sigma^*$
2. $x \leq y$ if there exists x', x'', y', y'' , ($y, y'' \neq \epsilon$) such that $x = x'x''$, $y = y'y''$ and $x' \leq y'$, $x'' \leq y''$.

\leq is the smallest relation satisfying (1) and (2).

Example:

$aba \leq aaba$

$aba \leq abca$

$aba \not\leq aabb$

Levels of Knowledge: Preliminaries

(X, \preceq) is

Levels of Knowledge: Preliminaries

(X, \preceq) is

a **partial order** if \preceq is reflexive, transitive and antisymmetric.

well founded if every infinite subset of X has a $(\preceq -)$ minimal element.

a **linear order** if it is a partial order and all elements of X are comparable.

Levels of Knowledge: Preliminaries

(X, \preceq) is

a **partial order** if \preceq is reflexive, transitive and antisymmetric.

well founded if every infinite subset of X has a $(\preceq -)$ minimal element.

a **linear order** if it is a partial order and all elements of X are comparable.

a **well-partial order** (WPO) if (X, \preceq) is a partial order and every linear order that extends (X, \preceq) (i.e., a linear order (X, \preceq') with $\preceq \subseteq \preceq'$) is well-founded.

Levels of Knowledge: Preliminaries

(X, \preceq) is

a **partial order** if \preceq is reflexive, transitive and antisymmetric.

well founded if every infinite subset of X has a $(\preceq -)$ minimal element.

a **linear order** if it is a partial order and all elements of X are comparable.

a **well-partial order** (WPO) if (X, \preceq) is a partial order and every linear order that extends (X, \preceq) (i.e., a linear order (X, \preceq') with $\preceq \subseteq \preceq'$) is well-founded.

A set $\{a_1, a_2, \dots\}$ of incomparable elements is a well-founded partial order but not a WPO.

Well-Partial Orders

Fact. (X, \preceq) is a WPO iff \preceq is well-founded and every subset of mutually incomparable elements is finite

Well-Partial Orders

Fact. (X, \preceq) is a WPO iff \preceq is well-founded and every subset of mutually incomparable elements is finite

Theorem (Higman). If Σ is finite, then (Σ^*, \leq) is a WPO

G. Higman. *Ordering by divisibility in abstract algebras*. Proc. London Math. Soc. 3 (1952).

D. de Jongh and R. Parikh. *Well-Partial Orderings and Hierarchies*. Proc. of the Koninklijke Nederlandse Akademie van Wetenschappen 80 (1977).

WPO and Downward Closed Sets

Given (X, \preceq) a set $A \subseteq X$ is **downward closed** iff $x \in A$ implies for all $y \preceq x$, $y \in A$.

Theorem. (Parikh & Krasucki) If Σ is finite, then there are only countably many \preceq -downward closed subsets of Σ^* and all of them are *regular*.

Levels of Knowledge

Theorem. Consider the alphabet $\Sigma_C = \{C_U\}_{U \subseteq \mathcal{A}}$. For all strings $x, y \in \Sigma_C^*$, if $x \preceq y$ then for all pointed models \mathcal{M}, s , if $\mathcal{M}, s \models yP$ then $\mathcal{M}, s \models xP$.

Levels of Knowledge

Theorem. Consider the alphabet $\Sigma_C = \{C_U\}_{U \subseteq \mathcal{A}}$. For all strings $x, y \in \Sigma_C^*$, if $x \preceq y$ then for all pointed models \mathcal{M}, s , if $\mathcal{M}, s \models yP$ then $\mathcal{M}, s \models xP$.

Incorrect as stated, but easily fixed: every extension of a WPO is a WPO

1. $K_1 K_1 \not\preceq K_1$
2. We should have $C_U \preceq C_V$ if $U \subseteq V$.

Levels of Knowledge

Theorem. Consider the alphabet $\Sigma_C = \{C_U\}_{U \subseteq \mathcal{A}}$. For all strings $x, y \in \Sigma_C^*$, if $x \preceq y$ then for all pointed models \mathcal{M}, s , if $\mathcal{M}, s \models yP$ then $\mathcal{M}, s \models xP$.

Incorrect as stated, but easily fixed: every extension of a WPO is a WPO

1. $K_1 K_1 \not\preceq K_1$
2. We should have $C_U \preceq C_V$ if $U \subseteq V$.

Corollary 1. Every level of knowledge is a downward closed set.

Levels of Knowledge

Theorem. Consider the alphabet $\Sigma_C = \{C_U\}_{U \subseteq \mathcal{A}}$. For all strings $x, y \in \Sigma_C^*$, if $x \preceq y$ then for all pointed models \mathcal{M}, s , if $\mathcal{M}, s \models yP$ then $\mathcal{M}, s \models xP$.

Incorrect as stated, but easily fixed: every extension of a WPO is a WPO

1. $K_1 K_1 \not\preceq K_1$
2. We should have $C_U \preceq C_V$ if $U \subseteq V$.

Corollary 1. Every level of knowledge is a downward closed set.

Corollary 2. There are only countably many levels of knowledge.

Realizing Levels of Knowledge

Theorem. (R. Parikh and EP) Suppose that L is a downward closed subset of Σ_K^* , then there is a finite Kripke model \mathcal{M} and state s such that $\mathcal{M}, s \models xP$ iff $x \in L$. (i.e., $L = Lev_{\mathcal{M}}(p, s)$).

States of Knowledge

S. Hart, A. Heifetz and D. Samet. *"Knowing Whether," "Knowing That," and The Cardinality of State Spaces*. Journal of Economic Theory 70 (1996).

States of Knowledge

Let W be a set of states and fix an event $X \subseteq W$.

Consider a sequence of finite boolean algebras $\mathcal{B}_0, \mathcal{B}_1, \mathcal{B}_2, \dots$ defined as follows:

$$\mathcal{B}_0 = \{\emptyset, X, \neg X, \Omega\}$$

$$\mathcal{B}_n = \mathcal{B}_{n-1} \cup \{K_i E \mid E \in \mathcal{B}_{n-1}, i \in \mathcal{A}\}$$

The events $\mathcal{B} = \cup_{i=1,2,\dots} \mathcal{B}_i$ are said to be **generated by** X .

States of Knowledge

Definition. Two states w, w' are **separated** by X if there exists an event E which is generated by X such that $w \in E$ and $w' \in \neg E$.

Question: How many states can be in an information structure (W, Π_1, Π_2) such that an event X separates any two of them?

States of Knowledge

Consider a K -list (E_1, E_2, E_3, \dots) of events generated by X .

We can of course, write down infinitely many infinite K -lists (**uncountably many!**).

States of Knowledge

Consider a K -list (E_1, E_2, E_3, \dots) of events generated by X .

We can of course, write down infinitely many infinite K -lists (**uncountably many!**).

Again, are they all consistent?

States of Knowledge

Consider a K -list (E_1, E_2, E_3, \dots) of events generated by X .

We can of course, write down infinitely many infinite K -lists (**uncountably many!**).

Again, are they all consistent?

Consider $(X, K_1X, \neg K_2K_1X, \neg K_1\neg K_2K_1X, K_2\neg K_1\neg K_2K_1X)$

States of Knowledge

Consider a K -list (E_1, E_2, E_3, \dots) of events generated by X .

We can of course, write down infinitely many infinite K -lists (**uncountably many!**).

Again, are they all consistent?

$(X, K_1X, \neg K_2K_1X, \neg K_1\neg K_2K_1X, K_2\neg K_1\neg K_2K_1X)$ is inconsistent.

Knowing Whether

Let $J_i E := K_i E \vee K_i \neg E$.

Lemma. Every J -list is consistent.

Theorem. (Hart, Heifetz and Samet) There exists an information structure (W, Π_1, Π_2) and an event $X \subseteq W$ such that all the states in W are separated by X and W has the cardinality of the continuum.

S. hart, A. Heifetz and D. Samet. "Knowing Whether," "Knowing That," and The Cardinality of State Spaces. Journal of Economic Theory 70 (1996).

What about beliefs?

In Aumann/Kripke structures belief operators are just like knowledge operators except we replace the truth axiom/property ($K\varphi \rightarrow \varphi$) with a consistency property ($\neg B\perp$).

What about beliefs?

In Aumann/Kripke structures belief operators are just like knowledge operators except we replace the truth axiom/property ($K\varphi \rightarrow \varphi$) with a consistency property ($\neg B\perp$).

Theorem. (R. Parikh and EP) There are uncountably many levels of belief.

What about beliefs?

In Aumann/Kripke structures belief operators are just like knowledge operators except we replace the truth axiom/property ($K\varphi \rightarrow \varphi$) with a consistency property ($\neg B\perp$).

Theorem. (R. Parikh and EP) There are uncountably many levels of belief.

What about probabilistic beliefs?

Bayesian Structures

- ▶ Let W be a set of worlds and $\Delta(W)$ be the set of probability distributions over W .
- ▶ We are interested in functions $p : W \rightarrow \Delta(W)$.
- ▶ The basic intuition is that for each state $w \in W$, $p(w) \in \Delta(W)$ is a probability function over W .
- ▶ So, $p(w)(v)$ is the probability the agent assigns to state v in state w . To ease notation we write p_w for $p(w)$.

Definition

The pair $\langle W, p \rangle$ is called a **Bayesian frame**, where $W \neq \emptyset$ is any set, and $p : W \rightarrow \Delta(W)$ is a function such that

$$\text{if } p_w(v) > 0 \text{ then } p_w = p_v$$

Given a Bayesian frame $\mathcal{F} = \langle W, p \rangle$ and a set of states S , an **Bayesian model based on S** is a triple $\langle W, p, \sigma \rangle$, where $\sigma : W \rightarrow S$.

Definition

For each $r \in [0, 1]$ define $B^r : 2^W \rightarrow 2^W$ as follows

$$B^r(E) = \{w \mid p_w(E) \geq r\}$$

Observation: We can define a possibility model from a Bayesian model as follows. Let $\langle W, p, \sigma \rangle$ be a Bayesian model on a state space S . We define a possibility model $\langle W, \mathcal{P}, \sigma \rangle$ base on S as follows: define $\mathcal{P} : W \rightarrow 2^W$ by

$$\mathcal{P}(w) = \{v \mid \pi_w(v) > 0\}$$

It is easy to see that \mathcal{P} is serial, transitive and Euclidean.

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

$$\pi_A:$$

	α	β	γ
α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

$$\pi_B:$$

	α	β	γ
α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

$$\pi_A:$$

	α	β	γ
α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

$$\pi_B:$$

	α	β	γ
α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*

Each player assigns probability 1/2 to E .

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

	α	β	γ
π_A : α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

	α	β	γ
π_B : α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*

Each assigns probability 1/2 to the other being sure of E

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

π_A :

	α	β	γ
α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

π_B :

	α	β	γ
α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*

Each assigns probability 1/2 to the other being sure of E

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

$$\pi_A:$$

	α	β	γ
α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

$$\pi_B:$$

	α	β	γ
α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*

Each assigns probability 1/2 to the other being sure of E

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

$$\pi_A:$$

	α	β	γ
α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

$$\pi_B:$$

	α	β	γ
α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*

A assigns probability 1/2 to B being sure she assigns probability 1/2 to E

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

	α	β	γ
π_A : α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

	α	β	γ
π_B : α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*

A assigns probability 1/2 to B being sure she assigns probability 1/2 to E

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

	α	β	γ
π_A : α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

	α	β	γ
π_B : α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*

A assigns probability 1/2 to B being sure she assigns probability 1/2 to E

Example

Let $N = \{A, B\}$, $\Omega = \{\alpha, \beta, \gamma\}$ and define π_A and π_B as follows:

$$\pi_A:$$

	α	β	γ
α	1/2	1/2	0
β	1/2	1/2	0
γ	0	0	1

$$\pi_B:$$

	α	β	γ
α	1	0	0
β	0	1/2	1/2
γ	0	1/2	1/2

Let $E = \{\alpha, \gamma\}$ and β be the *actual state*
and so on...

Hierarchies of Beliefs (Belief Frames)

Fix a state $w \in \Omega$ and a Belief Frame.

- ▶ **Ground Facts** $\Phi_0 = \{E \mid w \in E \text{ and } E \text{ a ground event}\}$

Hierarchies of Beliefs (Belief Frames)

Fix a state $w \in \Omega$ and a Belief Frame.

- ▶ **Ground Facts** $\Phi_0 = \{E \mid w \in E \text{ and } E \text{ a ground event}\}$
- ▶ **i 's first order beliefs:** $\Phi_i^1 = \{B_i(E) \mid E \text{ a ground event}\}$,
 $\Phi^1 = \Phi^0 \cup \cup_{i \in \mathcal{A}} \Phi_i^1$

Hierarchies of Beliefs (Belief Frames)

Fix a state $w \in \Omega$ and a Belief Frame.

- ▶ **Ground Facts** $\Phi_0 = \{E \mid w \in E \text{ and } E \text{ a ground event}\}$
- ▶ **i 's first order beliefs:** $\Phi_i^1 = \{B_i(E) \mid E \text{ a ground event}\}$,
 $\Phi^1 = \Phi^0 \cup \cup_{i \in \mathcal{A}} \Phi_i^1$
- ▶ **i 's second order beliefs:** $\Phi_i^2 = \{B_i(E) \mid E \in \Phi^1\}$,
 $\Phi^2 = \Phi^1 \cup \cup_{i \in \mathcal{A}} \Phi_i^2$

Hierarchies of Beliefs (Belief Frames)

Fix a state $w \in \Omega$ and a Belief Frame.

- ▶ **Ground Facts** $\Phi_0 = \{E \mid w \in E \text{ and } E \text{ a ground event}\}$
- ▶ **i 's first order beliefs:** $\Phi_i^1 = \{B_i(E) \mid E \text{ a ground event}\}$,
 $\Phi^1 = \Phi^0 \cup \cup_{i \in \mathcal{A}} \Phi_i^1$
- ▶ **i 's second order beliefs:** $\Phi_i^2 = \{B_i(E) \mid E \in \Phi^1\}$,
 $\Phi^2 = \Phi^1 \cup \cup_{i \in \mathcal{A}} \Phi_i^2$
- ▶ **i 's n -th order beliefs:** $\Phi_i^n = \{B_i(E) \mid E \in \Phi^{n-1}\}$,
 $\Phi^n = \Phi^{n-1} \cup \cup_{i \in \mathcal{A}} \Phi_i^{n-1}$.

Hierarchies of Beliefs (Belief Frames)

Fix a state $w \in \Omega$ and a Belief Frame.

- ▶ **Ground Facts** $\Phi_0 = \{E \mid w \in E \text{ and } E \text{ a ground event}\}$
- ▶ **i 's first order beliefs:** $\Phi_i^1 = \{B_i(E) \mid E \text{ a ground event}\}$,
 $\Phi^1 = \Phi^0 \cup \cup_{i \in \mathcal{A}} \Phi_i^1$
- ▶ **i 's second order beliefs:** $\Phi_i^2 = \{B_i(E) \mid E \in \Phi^1\}$,
 $\Phi^2 = \Phi^1 \cup \cup_{i \in \mathcal{A}} \Phi_i^2$
- ▶ **i 's n -th order beliefs:** $\Phi_i^n = \{B_i(E) \mid E \in \Phi^{n-1}\}$,
 $\Phi^n = \Phi^{n-1} \cup \cup_{i \in \mathcal{A}} \Phi_i^{n-1}$.

Thus each state in a belief models corresponds to the following infinite hierarchy of beliefs

$$(\Phi_0, (\Phi_i^1, \Phi_i^2, \dots)_{i \in \mathcal{A}})$$

Can this be done with Bayesian frames?

Can this be done with Bayesian frames?

First Order Beliefs: $\mu_{i,\omega}^1 \in \Delta(S)$ such that for all $s \in S$

$$\mu_{i,\omega}^1(s) = \sum_{\omega' \in \sigma^{-1}(s)} p_{i,\omega}(\omega')$$

Can this be done with Bayesian frames?

First Order Beliefs: $\mu_{i,\omega}^1 \in \Delta(S)$ such that for all $s \in S$

$$\mu_{i,\omega}^1(s) = \sum_{\omega' \in \sigma^{-1}(s)} p_{i,\omega}(\omega')$$

Second Order Belief: $\mu_{i,\omega}^2 \in \Delta(S \times [\Delta(S)]^{n-1})$ such that for all $s \in S$

$$\mu_{i,\omega}^2(s, (\mu'_j)_{i \neq j}) = \sum_{\omega': (\sigma(\omega'), (\mu'_j)_{i \neq j}) = (s, (\mu'_j)_{i \neq j})} p_{i,\omega}(\omega')$$

Can this be done with Bayesian frames?

First Order Beliefs: $\mu_{i,\omega}^1 \in \Delta(S)$ such that for all $s \in S$

$$\mu_{i,\omega}^1(s) = \sum_{\omega' \in \sigma^{-1}(s)} p_{i,\omega}(\omega')$$

Second Order Belief: $\mu_{i,\omega}^2 \in \Delta(S \times [\Delta(S)]^{n-1})$ such that for all $s \in S$

$$\mu_{i,\omega}^2(s, (\mu_j^1)_{j \neq i}) = \sum_{\omega': (\sigma(\omega'), (\mu_j^1)_{j \neq i}) = (s, (\mu_j^1)_{j \neq i})} p_{i,\omega}(\omega')$$

Given any state ω we have the following infinite hierarchy of beliefs

$$(\sigma(\omega), (\mu_{i,\omega}^1, \mu_{i,\omega}^2, \dots)_{i \in \mathcal{A}})$$

Refining the Questions

- ▶ For any given set S of external states we can use a Bayesian model or a type space on S to provide consistent representations of the players' beliefs.

Refining the Questions

- ▶ For any given set S of external states we can use a Bayesian model or a type space on S to provide consistent representations of the players' beliefs.
- ▶ Every state in a belief model or type space induces an infinite hierarchy of beliefs, but *not all consistent infinite hierarchies are in any finite model*. It is not obvious that even in an infinite model that all consistent hierarchies of beliefs can be represented.

Refining the Questions

- ▶ For any given set S of external states we can use a Bayesian model or a type space on S to provide consistent representations of the players' beliefs.
- ▶ Every state in a belief model or type space induces an infinite hierarchy of beliefs, but *not all consistent infinite hierarchies are in any finite model*. It is not obvious that even in an infinite model that all consistent hierarchies of beliefs can be represented.
- ▶ Which space is the “correct” one to work with?

Is there a universal (belief) space?

A **universal (belief) space** is a types space to which every type space (on the same space of states of nature and same set of agents) can be mapped, preferably in a unique way, by a map that preserves the structure of the type space.

If such a space exists, then the any analysis of a game could be carried out in this space without the risk of missing any “relevant” states of affairs.

Yes, if ...

The existence of a such a space depends on the topological and/or measure theoretic assumptions being made about the underlying state space S .

Yes, if ...

The existence of a such a space depends on the topological and/or measure theoretic assumptions being made about the underlying state space S .

First shown by Mertens and Zamir (1985)

The problem is to define the set of all infinite hierarchies of beliefs satisfying the same consistency properties (coherency and common knowledge of coherency) as that of hierarchies obtained at some state in a type space.

Kolomogorov Extension Theorem

Why do we care?

It turns out that finding the connection between rationality, what agents think about the situation and what actually happens depends on the existence of a “rich enough” space of types, i.e., a universal type space.

Why do we care?

It turns out that finding the connection between rationality, what agents think about the situation and what actually happens depends on the existence of a “rich enough” space of types, i.e., a universal type space.

It is not enough [...] that Ann should consider each of Bob's strategies possible. Rather, she considers possible both every strategy that Bob might play and every type that Bob might be. (Likewise, Bob considers possible both every strategy that Ann might play and every type that Ann might be.)

Brandenburger, Friedenberg and Keisler. *Admissibility in Games*. Econometrica 2009.

Overview of the Literature

- ▶ Existence proofs (under various topological assumptions):
[Armbruster and Boge, 1979], [Mertens and Zamir, 1985],
[Brandenburger and Dekel, 1993], [Heifetz, 1993], [Heifetz
and Samet, 1998], [Battigalli and Siniscalchi, 1999], [Meier,
2002], [Salonen, 2003]

- ▶ Impossibility Result: [Brandenburger and Kesiler, 2004],
[Meier, 2005]

Overview of the Literature

- ▶ Knowledge structures: [Fagin, Halpern and Vardi, 1991], [Heifetz and Samet, 1998], [Fagin, Geanakoplos, Halpern and Vardi, 1999]
- ▶ Relevant surveys: [Aumann, 1999], [Bonanno and Battigalli, 1999], [Brandenburger, 2002], [Brandenburger, 2005]
- ▶ Logic of type spaces: [Heifetz and Mongin, 2001], [Meier, 2001]

Brandenburger and Dekel

Assumption: Assume there are only two agents: i, j . Let the state space S be a Polish space (complete separable metric). For any metric space X assume that $\Delta(X)$ is endowed with the weak topology.

The proof proceeds as follows

1. Inductively construct the set of all possible types. Formally, types are infinite sequences of probability measures.

Brandenburger and Dekel

Assumption: Assume there are only two agents: i, j . Let the state space S be a Polish space (complete separable metric). For any metric space X assume that $\Delta(X)$ is endowed with the weak topology.

The proof proceeds as follows

1. Inductively construct the set of all possible types. Formally, types are infinite sequences of probability measures.
2. Define a notion of *coherency* such that if an individual's type is assumed to be coherent then it induces a belief over the types of the other individuals.

Brandenburger and Dekel

Assumption: Assume there are only two agents: i, j . Let the state space S be a Polish space (complete separable metric). For any metric space X assume that $\Delta(X)$ is endowed with the weak topology.

The proof proceeds as follows

1. Inductively construct the set of all possible types. Formally, types are infinite sequences of probability measures.
2. Define a notion of *coherency* such that if an individual's type is assumed to be coherent then it induces a belief over the types of the other individuals.
3. If common knowledge (in the sense of assigning probability 1) of coherency is assumed, then the set of beliefs is closed.

Step 1.

$$\begin{aligned} X_0 &= S \\ X_1 &= X_0 \times \Delta(X_0) \\ &\vdots \\ X_n &= X_{n-1} \times \Delta(X_{n-1}) \\ &\vdots \end{aligned}$$

A *type* t^i of i is an infinite sequence $t^i = (\delta_1^i, \delta_2^i, \dots) \in \prod_{n=0}^{\infty} \Delta(X_n)$

Let $T_0 = \prod_{n=0}^{\infty} \Delta(X_n)$.

Step 2.

Coherent: A type $t = (\delta_1, \delta_2, \dots) \in T_0$ is *coherent* if for every $n \geq 2$, $\text{marg}_{X_{n-2}} \delta_n = \delta_{n-1}$.

Coherency simply says that different levels of beliefs of an individual do not contradict one another. Let T_1 be the set of all coherent types.

Proposition There is a homeomorphism $f : T_1 \rightarrow \Delta(S \times T_0)$.

This is essentially *Kolmogorov's Existence Theorem*.

Note that the marginal probability assigned by $f(\delta_1, \delta_2, \dots)$ to a given event in X_{n-1} is equal to the probability that δ_n assigns to that same event.

Step 3.

We now impose “common knowledge” of coherency:

For $k \geq 2$ define

$$T_k = \{t \in T_1 : f(t)(S \times T_{k-1}) = 1\}$$

Let $T = \bigcap_{k=1}^{\infty} T_k$

This set T is the set we are looking for: the universal type space.

Proposition There is a homeomorphism $g : T \rightarrow \Delta(S \times T)$

Conclusions: Returning to the Motivating Questions

- ▶ How do states of knowledge influence decisions in *game situations*?
- ▶ Can we *realize* any state of knowledge?
- ▶ What is a *state* in an epistemic model?
- ▶ Is an epistemic model *common knowledge* among the agents?

Conclusions: Returning to the Motivating Questions

- ▶ How do states of knowledge influence decisions in *game situations*?
- ▶ Can we *realize* any state of knowledge?
- ▶ What is a *state* in an epistemic model?
- ▶ Is an epistemic model *common knowledge* among the agents?

Conclusions: Returning to the Motivating Questions

- ▶ How do states of knowledge influence decisions in *game situations*?
- ▶ Can we *realize* any state of knowledge?
It depends...
- ▶ What is a *state* in an epistemic model?
It depends...
- ▶ Is an epistemic model *common knowledge* among the agents?
It depends...

Thank You!